


General Features

Model	PSPXT 450-230	PSPXT 700-230	PSPXT 1250-230	PSPXT 450-230 USB	PSPXT 700-230 USB
Power rating	Off-Line				
Technology	450 VA - 270 W	700 VA - 420 W	1250 VA - 750 W	450 VA - 270 W	700 VA - 420 W
Input					
Voltage	230 VAC (197 - 262 VAC)				
Frequency	50Hz ± 4Hz; 60Hz ± 4Hz				
Amperage (maximum)	2.6 A	4.0 A	7.0 A	2.6 A	4.0 A
Output					
Voltage	230 VAC ± 10%				
Frequency	50Hz/60Hz ± 1Hz				
Wave form	STEP				
Battery					
Type	Valve-regulated, nonspillable, lead acid				
Quantity x Voltage x Rating	(1) x 12V x 7 Ah	(1) x 12V x 9 Ah	(2) x 12V x 7 Ah	(1) x 12V x 7 Ah	(1) x 12V x 9 Ah
Approved Battery Manufacturers	CSB, Panasonic, BB Battery and Yuasa				
Trasfer Time	< 10 ms typical				
Operating Back up time	> 10 minutes				
Recharge time	8hr up to 90%				
Connections					
Input sockets	1 x EN60320/C14				
Output sockets	3 x EN60320/C13	3 x EN60320/C13	4 x EN60320/C13	3 x EN60320/C13	3 x EN60320/C13
DB9 Communication port	contact closure			Serial (RS232)	
USB Port				Yes	
Surge Suppression Sockets	Yes				
Physical					
Dimensions wxhxd (mm)	80*176,5*233	80*176,5*233	92*238*283	80*176,5*233	80*176,5*233
Shipping Dimensions wxhxd (mm)	155*270*300	155*270*300	192*347*390	155*270*300	155*270*300
Net Weight, Kg	3.5	3.6	6.5	3.5	3.6
Gros Weight, Kg	4.5	4.6	7.9	4.5	4.6
Operating Environment					
Operation temperature	0°C to 40°C				
Storage Temperature	-15°C to 40°C				
Operation humidity	20% to 90%				
Packaging					
N° of output cables	2				
Multilink software CD	Yes				
Communication cables (contact closure and serial)	Yes				
USB cable				Yes	Yes
Standard warranty	2 years				
Warranty extention (1 or 3 years)	Available				

While every precaution has been taken to ensure accuracy and completeness in this brochure, Liebert Corporation assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions. © 2002 Liebert Corporation. All rights reserved throughout the world. Specifications subject to change without notice. All names referred to are trademarks or registered trademarks of their respective owners.



Liebert HIROSS UPS Headquarters
Via Gioacchino Rossini,6
20098 - S. Giuliano Milanese (MI)
tel.+39 02 982501 fax +39 02 98250273
info.ups@liebert-hiross.com

Liebert HIROSS Services Headquarters
Via Leonardo da Vinci,8
35028 - Piove di Sacco (PD)
tel.+39.049 9719111 fax +39 049 5841257
service@liebert-hiross.com

Liebert HIROSS United Kingdom
Globe Park - Marlow - Bucks - SL71YG
tel.+44 1628 403236 fax +44 1628 403294



PowerSure Personal XT 450 - 700 -1250VA
Serial / USB Comms

COMPREHENSIVE POWER PROTECTION FOR STAND-ALONE SYSTEM



NEW

PowerSure Personal XT

COMPREHENSIVE POWER PROTECTION FOR STAND-ALONE SYSTEM



Thanks to the new PowerSure Personal XT you can have continuous cost-effective power protection in your office or home.

It is specifically designed to protect PCs, Workstations, Network Nodes and also Fax, Scanners and Audio/Video equipment.

If the mains supply fails or moves outside an acceptable level, the PowerSure Personal XT offers up to 20 minutes of battery back up (depending on the actual load), giving ample time to protect the equipment and save files through Liebert's WEB based Multilink Software.

Benefits


- Protection up to 1250 VA
- Small Dimensions
- Plug and Play Operation
- Up to 4 output sockets
- Direct and Remote Monitoring
- Serial / USB communications
- MultiLink Software included
- All communication cables included
- Attractive design
- Phone, modem, data-lines surge suppression sockets

Applications

- PCs
- Workstations
- Small Servers and Network Nodes
- Fax
- Scanners
- Audio/Video equipment

MultiLink Software

- Multilink Software is the world's first UPS Software to be written in Java
- Operating with any Liebert UPS (including the Personal XT), it protects the network PCs or Servers from crashes caused by power failure
- Prevents the loss of valuable data by performing unattended, orderly shutdown on one computer or multiple networked computers with optional license kit
- Configurable responses to UPS status changes
- Notification via alphanumeric pagers, e-mail and on-screen messages
- It runs as part of an enterprise-wide SNMP solution or as stand alone shutdown management for a single file server
- Supports both serial interface and contact closure interface
- Manage and monitor UPSs over the network with optional license kit





Major Features

■ Protection up to 1250 VA

The PowerSure Personal XT is available in 3 power ratings: 450, 700, 1250 VA and covers all the applications from single PCs to network nodes through multiple workstation.

■ The smallest ups in its range

The high frequency design of the PowerSure Personal XT results in a very compact UPS. It can operate on your desk or on the floor, in vertical or horizontal position, protecting your computer equipment and your data using very little space.

■ Plug and play



The PowerSure Personal XT is very easy to use: the simple operation and the two LEDs provide you clear and complete information about the UPS status.

■ Serial (RS232) and USB communication Features

450 and 700 VA ratings are also available in Serial + USB configuration. The Serial communication allows to fully benefit from all the various monitoring features of MultiLink Software and related scheduled actions. The USB communication, initially operating only through Windows 2000 / XP native Power Manager, will be soon fully supported by MultiLink Software. The USB port will offer a much faster data exchange (up to 7 times faster than Serial port), the capability to connect the UPS to a USB peripherals chain (very common in current PC configurations), hot swapping capabilities, automatic detection of the UPS (when managed through Windows 2000 / XP).

■ Everything you need is in the box

The PowerSure Personal XT comes complete with: User Manual, two output power cords communication cables, MultiLink software CD.



■ Little maintenance

The PowerSure Personal XT requires very little maintenance: only the 5-years battery requires replacement. An automatic battery test verifies battery conditions and, if they are bad, a specific alarm is activated.

■ Output connection flexibility

The PowerSure Personal XT is equipped with up to four UPS protected output sockets to allow the maximum of flexibility in connecting several loads.

■ Phone and network surge suppression sockets

Surge sockets protect sensible hardware against voltage surges coming from lines (such as modem, fax, phone, network connections) which can seriously damage comms ports, motherboards, etc...

■ Direct and remote monitoring

The contact closure or serial DB9 port and the USB port together with MultiLink Software (provided) allow you to monitor your PowerSure Personal XT or to shut down your PC directly through the cable (provided) or remotely through the Net.

■ More features

Standard features include automatic battery test and "autorestart" function (the UPS automatically restarts when mains comes back after an extended outage and full discharge of the battery). Audible and visual alarms for mains failure, low battery, UPS overload, short circuit, and over temperature are available.

■ Attractive design

The PowerSure Personal XT, with its ergonomic shape was specifically designed to be an attractive addition to any office or home.